

# BITUMINOUS FILLET

**DESCRIPTION:**

Bitumen rubber based elastic fillet in triangle form to shape interior corners appropriate for bituminous waterproofing applications at connection points of horizontal and vertical structure parts.

**APPLICATION AREAS:**

It can be used to shape the interior corners at applications with self adhesive or torch applied bituminous membranes.

It can be used at connection corners of differently expanding construction elements.

It can be used at both solvent or water based liquid membrane applications.

**TECHNICAL PROPERTIES:**

|                    |                           |
|--------------------|---------------------------|
| SIDE SIZE          | : 25mm X 25mm X 35mm      |
| SOFTENING POINT    | : 90°C                    |
| PENETRATION (25°C) | : 40-50 dmm               |
| ELASTIC RECYCLING  | : 75%                     |
| SPECIFIC WEIGHT    | : 1,30 kg/dm <sup>3</sup> |

**ADVANTAGES:**

Quick and easy application.

Permanent high elasticity at temperatures between -15°C to +90°C.

Perfect adhesion to many different construction materials.

**SURFACE PREPARATION AND APPLICATION:**

The application area should be dry and clean. To obtain better adhesion, the concrete surfaces should be primed with EMILKOTE® and metal surface should be primed with EMÜLZER® C. Cut the tape to required length. Melt protective PE cover by torching or hot air welding. Press the tape to corner securely. The insulation application can proceed further instantly.

**CONSUMPTION:**

It depends on dimensions of the profile.

**PACKAGING:**

1,2mx21tapes in box.(25,2m/box)

Roll dimensions: 40mm X 40mm X 5,7mm X 1,2 m.

**SAFETY PRECAUTIONS:**

Keep out of reach of children.

The eyes and the skin should be protected while working with all kinds of chemicals.

Never add spirits, gasoline or any other liquids to hot bitumen. Special equipment should be used while working with hot bitumen.

Because this bulletin has been prepared considering the general conditions only, for the details except for the ones written above, please request additional written information otherwise no responsibility will be assumed due to the faults arising because of the insufficient data.

This technical bulletin invalidates the previous ones regarding this product.

EMÜLZER ASFALTEVİ TECRİT MADDELERİ SANAYİ VE TİCARET LİMİTED ŞİRKETİ

Cebeci Caddesi No 73 Küçükköy 34100 İstanbul

Telephone: +90(212)5372500 PBX – Fax: +90(212) 6172380

[www.emulzer.com.tr](http://www.emulzer.com.tr)

